## **HEAVY DUTY SILAGE FORK**

http://tiny.cc/silagefork



## **FEATURES & BENEFITS**


- Heavy duty frame (except mod. 80)
- Versatile and efficient
- Replaceable teeth
- Compact model, which is well suited for silage distributing in small and confined places

The multi-purposed silage fork, in combination with the frame top hydraulic clamp, makes moving loose or baled silage safe and easy. The extra strength framework allows heavy loads, like round bales, to be safely and effectively moved. The lower fork teeth are easily removed and replaced when worn (except mod. 80).



Model	Width	Teeth length	Nr. of teeth	Weight	Code
80	80 cm (31.5 in)	48 cm (18.9 in)	5	67 kg (148 lbs)	C895061
95	95 cm (37.4 in)	60 cm (23.6 in)	6	88 kg (194 lbs)	C890355
120	120 cm (47.3 in)	60 cm (23.6 in)	8	110 kg (242 lbs)	C890356
150	150 cm (59 in)	60 cm (23.6 in)	9	130 kg (287 lbs)	C890357

Compatibility	\\.\.	<u>ئ</u> .	NJ.	ري. بي	ويزې	6.	رئ	8/4	900.	0'è	1000	6.55	13, KS	die	5. <sub>x</sub>	€
Model																
80																
95																
120																
150																
(*) C890025 adapter required																



Very compatible

Compatible

Not compatible