TRENCHER

http://tiny.cc/trencher



FEATURES & BENEFITS

Minimal damage to the ground on trenching area

Digs from 14 to 20 cm (5.5 to 7.9 in) wide trench and moves all ground to the right side of the trench

Very fast and clean way to dig trenches for cables, drains, piping etc.

With MultiOne and trencher you can easily dig narrow trenches without damaging the ground on the digging area. The trencher does a clean trench which can easily be filled with a bucket or a dozer blade. Planetary drive with hydraulic motor guarantee powerful and trouble free operation. Max digging depths are 60, 90 and 120 cm (35.4, 23.6 and 47.2 in) respectively, depending on model. Digging width is either 14, 16, 18 or 20 cm (5.5, 6.3, 7.1 or 7.9 in), every chain tools kit can be set for different widths. Hard ground version chains have tungsten reinforcements to ensure long lasting performance in hard and rocky soil, otherwise the standard version is the best choice for vegetative ground.

• Trencher is ideal for smaller cable or pipe laying.

• Digging speed with a trencher is 2-3 times quicker compared to a backhoe.

• Combination of an articulated MultiOne and trencher leaves almost no marks of digging operations after the work is done. This makes it a perfect solution for gardens and other lawn areas.

It features an adjustable depth control foot which ensures the operator digs at a set depth at all times and efficient spoil removal for effective compaction back into the trench.

Model	Max Digging Depth		Max Digging Width	\	Weight	Code		
Trencher 60 w/o chain tools ¹	60 cm (23.6 in)	14 to	20 cm (5.5 to 7.9 in)	205,5	kg (453 lbs)	C890206		
Trencher 90 w/o chain tools ¹	90 cm (35.4 in)	14 to	20 cm (5.5 to 7.9 in)	235 l	kg (518 lbs)	C890207		
Trencher 120 w/o chain tools ¹	120 cm (47.2 in)	14 to	20 cm (5.5 to 7.9 in)	248 l	kg (547 lbs)	C890208		
Chain tools	Trencher 60		Trencher 90		Trencher 120			
Tools kit for soft ground ²	C891002		C891003		C89	21004		
Tools kit for hard ground ²	C891005		C891006		C891007			

(1) Chain tools kit required. (2) Trencher required.

					^{رېر} ڼ ښ				°€>		~&_	60	3	ري د	*	
Compatibility	\\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\	J.;	NJ.	<i>4</i> 5.7	27,3	6.5	√ي.	8,4	00.00	0 Ö	12.0	6.32	13/12	olizzo	15/4	€Z-
Model																
60 - soft groud																
90 - soft groud																
120 - soft groud																
60 - hard groud																
90 - hard groud																
120 - hard groud																
(*) C890025 adapter required		<u> </u>					Very compatible			Compatible			Not o	compatib	le	