LAWN MOWER

http://tiny.cc/lawnmower2



- Equipped with automatic stop valve
- Floating system guarantees easy operation and good mowing result also on uneven lawns
- Rear or side discharge as standard, mulching kit available as an option
- Four puncture free tires

Ideal for fine cut applications, such as golf courses and large acreage mowing. The mower has been designed with three blades (two blades on mod. 100) that cut with an overlap that prevents uncut strips.

MultiOne's extensive design experience makes the mower very reliable and assures a high quality cut. The independent four wheel support of the mower frame allows the mower deck to follow ground contours. It is equipped with the MultiOne floating system, which guarantees optimal touch with the ground also on uneven lawns. The mower is also equipped with a automatic stop valve which stops the blades when the mower is lifted off the ground. Moreover, thanks to the MultiOne telescopic boom, it is possible to cut the grass even under trees and bushes where the conventional mower could not reach. The mower mod. 100 is mulching type as standard. Mulching kit is available as an option on model 130, 150 and 180.

Note: the floating boom valve on machine is required.

Model	Width	Cutting Height	Weight	Code	
Lawn mower 100 with mulching system	100 cm (39.4 in)	1-12 cm (0.4 – 5 in)	116 kg (256 lbs)	C895080	
Lawn mower 130 with rear discharge	130 cm (51.2 in)	1-12 cm (0.4 – 5 in)	170 kg (375 lbs)	C890636	
Lawn mower 150 with right side discharge	150 cm (59 in)	1-12 cm (0.4 – 5 in)	207 kg (457 lbs)	C890632	
Lawn mower 180 with left side discharge	1-12 cm (0.4 – 5 in)	240 kg (529 lbs)	C890634		
Options					
Mulching kit for lawn mower 130			20 kg (44 lbs)	C890631	
Mulching kit for lawn mower 150			21 kg (47 lbs)	C890633	
Mulching kit for lawn mower 180			25 kg (55 lbs)	C890635	
	- 1 1	- 1		1 1	

Compatibility	`.	رئ	٣'n	<i>₹</i> 3.	⁶	<i>6</i> .5	√ي	8/4	800.00	0'è	10,00	(igs)	13/20	o jesti	15.X	£1
Model	ì			.5		0		0		-5		J		-5		Ť
100																
130																
150																
180																
(*) C890025 adapter required							Ven	, compati	hle		Compa	atible		Not	compatible	le

