

# DROP SPREADER

<http://tiny.cc/dropspreader>



## FEATURES & BENEFITS

- Self-loading design.
- Adjustable stop springs for salt distribution, present throughout the entire length of the system.
- Distributor roller: the pegs are positioned in helical position to assure continuous and proportioned distribution.
- Protective netting: a protective metallic mesh net is fixed on the top of the salt loading vat.
- Internal mixer axle which breaks any frozen salt and prevents the salt from clogging up.

The drop spreader is designed for fast and efficient spreading. Front mounting allows loading from ground level in the same way as with normal bucket. Powered by hydraulic motor and equipped with a mixer axle which breaks any frozen salt and prevents the salt from clogging up. It is ideal to spread salt or sand on parking lots, sidewalks, bicycle lanes and pedestrian areas.



Model	Volume*	Width	Spreading Width	Height	Weight	Code
110	470 l (16.6 ft <sup>3</sup> )	125 cm (49.2 in)	110 cm (43.3 in)	100 cm (39.4 in)	270 kg (595 lbs)	<b>C890189</b>
130	580 l (20.5 ft <sup>3</sup> )	145 cm (57 in)	130 cm (51 in)	100 cm (39.4 in)	330 kg (728 lbs)	<b>C890188</b>

(\*) verify the lifting capacity of the machine

Compatibility	1.1	2.3	4.2	5.2	5.3	6.3	7.2 7.3	8.4	8.15 8.16	9.6	10.8 10.9	6.3SD	7.3SD 8.4SD	9.5SD	12.4*	EZ
Model																
110																
130																

(\*) C890025 adapter required

